

PRODUCT SHEET



A302 -2733 RHIAN S3 SRC

Safety mid shoes with composite toe cap and antiperforation non-metallic midsole

Standard: EN ISO 20345:2011

Range of size: 36-47 (EU)

The footwear is designed to comply with the provisions of the Regulation EU 2016/425 and the essential safety and health requirements corresponding to the intended use area.

Field of use: protection of the forefoot against impact (200J mechanical shocks) and crushing (15kN static compression force), protection of the foot against puncture (1100N perforation force), minor superficial mechanical aggressions (abrasion, clamping), heel protection against mechanical shocks (properties of energy absorption in the heel, minimum 20J), antistatic properties and outsole with profile, resistant to hydrocarbons - to handling activities of heavy objects with danger of falling or rolling, when traveling on uneven surfaces or covered with shallow layers of water.

Applications and industries: construction, industry, logistics, maintenance, general use.

Characteristics and materials:

- ✦ Upper: water repellent, printed leather;
- ✦ Vamp lining: nonwoven fabric;
- ✦ Quarter lining: loose knit fabric with spongy material;
- ✦ Removable insole: non-woven, stiffened fabric, antistatic;
- ✦ Sole: dual density PU, directly injected, non-slip surface;
- ✦ Ankle protection: provided at the upper edge with a cushioning comfort element made of synthetic leather, doubled with spongy materials;
- ✦ Toecap: composite;
- ✦ Antiperforation midsole: non-metallic;
- ✦ Closing system: laces by means of perforations reinforced with anti-corrosion protected staples
- ✦ Width: 11 mondopoint
- ✦ Quarter height: minimum 125 mm assortment B;
- ✦ **Performances according to EN ISO 20345:2011:**
 - ✓ Safety toecap with shock resistance of 200J
 - ✓ Safety toecap with resistance to compression forces of 15 kN
 - ✓ The lower assembly withstands a perforation force of 1100N
 - ✓ Abrasion resistant outsole - relative volume loss is below 150 mm³, for materials whose density is over 0.9 g / cm³
 - ✓ Outsole resistant to hydrocarbons - volume variation after immersion during (22 ± 2) h in isooctane is below 12%, and the hardness increase below 10 Shore degrees



+40 265 264 817

- ✓ ± 2) h in isooctane is below 12%, and the hardness increase below 10 Shore degrees
- ✓ Water resistance: Resistance of the upper assembly to penetration and water absorption (water absorption is not more than 30% after 60 minutes from the beginning of the test and no penetration of more than 2g after another 30 minutes.
- ✓ Shock absorption: energy absorption in the heel (minimum 20 J)
- ✓ Antistatic footwear - resistance between 100k Ω and 1000 M Ω

Maintenance, cleaning instructions: The footwear incorporates both natural and synthetic materials. It has to be stored in a cool, dry, clean place, preferably in the original packaging. During use it should be cleaned regularly, using a damp cloth, including inside, to remove dirt and contaminants from the upper assembly and the sole. No sharp objects are used when cleaning. If the shoe has become damp, it should be dried naturally in an open, cool and well-ventilated area. It should not be exposed to direct heat or radiation. After drying, it is recommended to treat the upper with oily cream, or wax or other good quality substances, especially for the leather.



+40 265 264 817