

PRODUCT SHEET

A021 – 2010CNO1 Sandale New Azure O1 SRC

Work sandals O1 SRC without toecap protection



Standard: EN ISO 20347:2012

Range of size: 35-47 (EU)

The footwear is designed to comply with the provisions of the Regulation EU 2016/425 and the essential safety and health requirements corresponding to the intended use area.

Field of use: protection against minor superficial mechanical aggressions (abrasion, clamping), heel protection against mechanical shocks (properties of energy absorption in the heel, minimum 20J), antistatic properties.

Applications and industries: constructions, logistics, maintenance, general use.

Characteristics and materials:

- ✧ Upper: suede leather;
- ✧ Lining: textile;
- ✧ Removable insole: non-woven, antistatic;
- ✧ Sole: dual density PU, directly injected, non-slip surface;
- ✧ Ankle protection: provided at the upper edge with a cushioning comfort element made of synthetic leather, doubled with spongy materials;
- ✧ Closing system: tongue for sandals;
- ✧ Quarter height: min. 75 mm assortment A;

Performances according to EN ISO 20347:2012:

- ✓ Abrasion resistant outsole - relative volume loss is below 150 mm³, for materials whose density is over 0.9 g / cm³
- ✓ Shock absorption: energy absorption in the heel (minimum 20 J)
- ✓ Antistatic footwear - resistance between 100k Ω and 1000 M Ω
- ✓ Slip resistance:
 - Slip resistance on ceramic tile floors, greased with detergent solution:
 - coefficient of friction condition A - sliding the heel forward: ≥ 0.28 ;
 - coefficient of friction condition B - sliding the sole forward: ≥ 0.32 ;
 - Slip resistance on steel floors, greased with glycerin:
 - coefficient of friction condition C - sliding the heel forward: ≥ 0.13 ;
 - coefficient of friction condition D - sliding the sole forward: ≥ 0.18 .

Maintenance, cleaning instructions: The footwear incorporates both natural and synthetic materials. It has to be stored in a cool, dry, clean place, preferably in the original packaging. During use it should be cleaned regularly, using a damp cloth, including inside, to remove dirt and contaminants from the upper assembly and the sole. No sharp objects are used when cleaning. If the shoe has become damp, it should be dried naturally in an open, cool and well-ventilated area. It should not be exposed to direct heat or radiation. After drying, it is recommended to treat the upper with oily cream, or wax or other good quality substances, especially for the leather.



+40 265 264 817