

TECHNICAL DATASHEET

5X1300000

Rev.00



FEATURES:

- Platform System
- SoftPad Technology
- Lens with FLD (Floating Lens Design) technology
- Extended 9 base wraparound lens, provides extra coverage around the eyes
- Adjustment of temples in length and inclination
- Soft patented nose pad in anallergic rubber, with height adjustment and designed to reduce pressure on the nose
- Fast interchange of the temples with elastic band
- Fast Interchangeable lenses system
- Easy assembly of the rubber gasket

FRAME FEATURES:

Frame Typology	Spectacle
PPE field of view	>40°
Temple adjustment	Inclination and Length
Weight (g)	28
Size	---
Material Features	Anallergic

FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	Polycarbonate
Colour	Claer
Technical Treatment	Antiscratch
Aesthetic Treatment	I/O
Thickness	1.9
Curvature	Base 9 Spheric
Optical Class	1
UV Protection	400 nm
Spare parts	-
VLT% (+/-5%)	57.3

MARKING DATA:

Standard References	EN166 EN170 EN172
Frame Marking	Mod.5X1 U EN166 FT CE
Ocular/Flip-up Marking	2C-1.7/5-1.7 U 1 FT CE

APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T);

Notes

Corrective version available (Caliber: 55 - 21) - Wide range of lenses available

