

USER INSTRUCTIONS

PRODUCT CODE: C209 - 1469 HPT BLUE

Safety category: II

GLOVE DESCRIPTION: Knitted Wrist with PVC-HPT coating on nylon lining palm, front & back of fingers/thumb. Tough flexible PVC Sponge Touch finish coating using hydropellent technology, provides the highest level of grip and soaks up the oil to ensure the hand won't slip in oil conditions.

Available sizes: 5(XXS)-12(XXXL)

Sizes	5/XXS	6/XX	7/S	8/M	9/L	10/XL	11/XXL	12/XXXL
Hand size according to EN ISO 21420:2020	5	6	7	8	9	10	11	12

USE: Greater dexterity and grip in dry and wet applications. Light weight with non-slip surface. Seamless nylon liner allows to breath and produces minimal lint Dexterity and grip with durability makes this glove an economical choice. Actifresh /Sanitized treated to provide some protection against organisms which give rise to bad odour and cross infection. Not recommended for liquid chemicals. Protection levels are measured from palm area of glove. The gloves shall not be worn when there is a risk of entanglement with moving parts of machines.



EN 388:2016+A1:2018



3131X

Protection against mechanical risks

3 Abrasion Resistance (Min 0, Max 4)
1 Cut Resistance (Min 0, Max 5)
3 Tear Resistance (Min 0, Max 4)
1 Puncture Resistance (Min 0, Max 4)
X TDM Cut (ISO 13997) (Min A, Max F)

X means test not tested

Protection levels are measured from palm area of glove.

Dexterity performance level is 5 in accordance with EN ISO 21420:2020.

The gloves are tested according to the standards EN ISO 21420:2020, EN388:2016+A1:2018.

EU type examination carried out by SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland Notified Body No. 2777 in accordance with Regulation EU 2016/425.

MARKING: Name of manufacturer, Style, Size, Actifresh or Sanitized. CE Mark and mechanical pictogram with performance levels.

Glove doning: Ensure the selection of appropriate glove size. Check for any physical damages, glove condition and contamination prior to each use of glove.

Glove doffing: Remove the glove as soon as it wear off or damaged. It is advisable to ease left and right gloves off alternately using the gloved hand so that the gloves are removed without contacting bare hands.

STORAGE: Gloves should be ideally stored at 5-25 °C in dry, well-ventilated area in original packing. Prevent direct sunlight.

CLEANING/MAINTENANCE: Excess contaminant should first be removed and the gloves may be decontaminated with rinse water then rinsed with clean water and dried ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternately using the gloved hand so that the gloves are removed without the contaminant contacting bare hands.



+40 265 264 817

LIMITATION OF USE / RISK: Gloves are intended to protect hands in working environment in accordance with EN388:2016+A1:2018 and EN ISO 21420:2020. The user shall evaluate and determine risks based on intended application and use gloves only in intended application. Risk should be evaluated keeping in mind the protection levels and the harmonized standards on which gloves are tested. The described gloves have been evaluated by testing to EN388:2016+A1:2018 and EN ISO 21420:2020 and Regulation EU 2016/425 and covers all reasonably foreseeable risks.

OBsolescence/Disposal: When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the glove for its intended use.

GENERAL: None of the raw materials or processes used in the manufacture of these products is known to have any harmful effect on the wearer. Please note that the results of the tests should help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer to determine glove suitability to the intended use. Further information may be obtained from manufacturer.

The declaration of conformity and the technical sheet can be downloaded at: <https://magazin.renania.ro/>

Further information available from:

Renania Trade S.R.L. str. Dezrobirii no.19, Targu Mures, Romania



+40 265 264 817